













Manufactured by:
PT. Bangunperkasa Adhitamasentra

Bangunperkasa Adhitamasentra is a pioneer fiber cement board manufacturer in Indonesia with the brand "GRC board" .The first plant was located in Citeureup, west Java, this plant was established since 1992 and have started the production in 1994, and because of the increasing of customer's satisfaction to GRC board products, we established the second plant in 2010, which was located at Karawang, to meet the demand of the market. The technology that is applied is from Japan, and our product quality is of International standard.

Other than replacing the function of plywood & gypsum board, GRC board product makes beautiful the building and requires minimum maintenance.

GRC board is very suitable for any kind of application such as: ceiling, partition, underlay roof, cubical toilet, cladding, façade, flooring and decorative wall. GRC board product offers the best quality, strength that is required, easy to apply and economical.

Our factory is supported by independent R&D Department that focus on process and product development. Learning from our experiences in more than two decades, we manufactured and adjust our product to fulfill the demand and the developments of the market, and always put quality and costumer service is our top priority.

GRC Board has advantages:

- 1. 100% No Asbestos content
- 2. Strong and resistant to impact
- 3. Resistant to water and humidity
- 4. Resistant to fire
- 5. Resistant to fungi
- 6. Resistant to termites
- 7. Soundproof
- 8. Smooth surface and easy to paint
- 9. Easy application with nail or screw

The certification that has been obtained by GRC board is:

- 1. ISO 9001: 2015 for design/development and manufacture of non asbestos fiber cement boards
- 2. Fire resistance, depends on the result of the SNI 1741-2008 equal to JIS 1304
- 3. ISO 140: Measurement of sound Insulation in building and Buildings element
- 4. SNI 8299 Non asbestos flat cement board
- Green Label Certificate from Green Product Council Indonesia

And has received several awards such as:

- Has selected as home preferred brand award for category the best ceiling system 2017
- 2. As Circle founder member from Green product council Indonesia
- 3. Idea best readers choice for category wall panel system 2010
- Award from Museum Record Indonesia (MURI) by building 36 habitable houses in less than 24 hours in 2015
- 5. Has selected as Home Architect Choice

Variety of Products

A. GRC board

Applied for interior application, this variety name same as our brand. Avaiable with square edge or recesses edge

Dimension and Application

H x W x L (mm)	Weight (kg)	Application
4 x 600 x 1200	4.7	Ceiling
4 x 1220 x 2440	19	Centring
5 x 1220 x 2440 / 3000	24 / 28	
6 x 1220 x 2440 / 3000	28 / 34	Ceiling & Partition
8 x 1220 x 2440 / 3000	38 / 46	Partition
10 x 1220 x 2440 / 3000	46 / 58	rantition

^{*}Available to customize dimension & thickness with condition apply





B. GRC Superpanel

Very suitable and practical to be applied as exterior application to deal with extreme weather

Dimension and Application

H x W x L (mm)	Weight (kg)	Application
9 x 1220 x 2440	42	Cladding / Facade
12 x 1220 x 2440	56	Cladding / Facade

*Available to customize dimension with condition apply





C. GRC Superplank

For replacing the wood material with bevel edge. There is 2 type bevel: BV1 and BV2

Dimension and Application

H x W x L (mm)	Weight (kg)	Application	
9 x 75 x 2440 BV1/BV2	3	Plint / Skirting	
9 x 100 x 2440 BV1/BV2	4	Lisplank / Skirting / Siding	
9 x 200 x 2440 BV1/BV2	8	Lisplank / Siding	
9 x 300 x 2440 BV1/BV2	11		

*Available to customize dimension with condition apply







D. GRC Simpleplank

Is a product of GRC board that is made and designed with square edge to fit with application on minimalist design.

Dimension and Application

H x W x L (mm)	Weight (kg)	Application	
8 x 100 x 2440	3	Listplank / Skirting / Siding	
8 x 200 x 2440	6		
8 x 200 x 3000	8	Listplank / Siding	
8 x 300 x 2440	9		
8 x 300 x 3000	11		

*Available to customize dimension with condition apply





E. GRC Timberplank

Is very suitable for plank application on the building that require wood concept design. To emphasize the motif of the wood, it is recommended to paint the product with the wood paint/polish.

Dimension and Application

H x W x L (mm)	Weight (kg)	Application	
8 x 100 x 2440	3	Listplank / Skirting / Fence / Siding	
8 x 200 x 2440	6		
8 x 200 x 3600	10	1	
8 x 200 x 4000	12	Listplank /	
8 x 300 x 2440	9	Fence / Siding	
8 x 300 x 3600	15		
8 x 300 x 4000	17		

^{*}Available to customize dimension with condition apply





F. GRC Deco Plank

Is product which give more edge to the design, it is very suitable for decorative application on any building that need concept design.

Dimension and Application

T x W x L (mm)	Weight (kg)	Application
9 x 200 x 1200	<u>+</u> 2.5	Listplank
9 x 300 x 1200	<u>+</u> 3.0	Listpiarik

^{*}Available to customize dimension with condition apply





G. GRC Deco Panel

GRC Decopanel series gives an unique decoration for interior and exterior the decorative panel from GRC board is a suitable choice because it has many design available for décor or could be costumized base on costumers request.

Dimension and Application

Thickness	Width	Length	Application
(mm)	(mm)	(mm)	
6 - 20	Max. 3000	Max. 1220	Wall, Partition, Sketsel, Ceiling, etc

^{*} Available to customize design and dimension with condiition apply

There are 3 types of GRC Deco Panel product motives:

- 1. GRC Deco Panel Motive
- 2. GRC Deco Panel Line
- 3. GRC Deco Panel Brick





H. GRC Mahoni plank

One of the products from the GRC board is to replace the wooden board material with the wood surface. It is recommended to use wood paint so it can look natural.

Dimension and Application

T x W x L (mm)	Weight (kg)	Application	
8 x 100 x 3000	3		
8 x 200 x 3000	8	Lisplank / Siding / Fence	
8 x 300 x 3000	11		

*Available to customize dimension with condition apply



I. GRC Mahoni deck

A product from GRC board with wood surface so that the floor feels and looks like wood, wood paint is highly recommended to get the impression of natural wood.

Dimension and Application

T x W x L (mm)	Weight (kg)	Application	
20 x 100 x 2400	7.5	Decking	
20 x 200 x 2400	15.5		
20 x 300 x 2400	23.4		

^{*}Available to customize dimension with condition apply





J. GRC Superdeck

Is product that applied for floor with camber edge in both side and smooth surface

Dimension and Application

T x W x L (mm)	Weight (kg)	Application	
20 x 100 x 2400	7.5	Decking	
20 x 200 x 2400	15.5		
20 x 300 x 2400	23.4		

*Available to customize dimension with condition apply



K. GRC Superfloor

Is product that applied for floor with square edge in both side and smooth surface.

Dimension and Application

Thickness (mm)	Width (mm)	Length (mm)	Weight (kg)	Application
15	1220	2440	70	Floor
20	1220		95	FIOOL

*Available to customize dimension with condition apply



We guarantee that our products are sold in good condition without damage or fault caused by faulty production or its raw materials.

PRODUCT GUARANTEE

This product warranty does not cover damage caused by:

- 1. Transportation and or it's agent sending the goods to the customer as it is out of the company's control.
- 2. Installation quality and system of workers as various factors affect good and right installation system.
- 3. Suitability of our product on particular application which are not according to our recommendations.

MAKE SURE THAT GENUINE PRODUCT IS PRINTED WITH 'GRC board' ON THE PRODUCT











Strong and



Termites Resistant



Humidity Resistant



Manufactured by:

PT. BANGUNPERKASA ADHITAMASENTRA

GRAHA GRC board

Jl. S. Parman Kav. 64 Lantai 3, Jakarta Barat 11410

Telp. : (021) 53 666 800 (hunting)

Fax. : (021) 53 666 720
Website : www.grcboard.com
Email : marketing@grcboard.com



SCAN ME



www.grcboard.com

Accessories

GRC Compound A+B

This compound is used to fill the gap between the joins of the the GRC board.

Packaging	Weight	Descriptions
Tip	2 kg	1 set for <u>+</u> 35 m2
Tin	8 kg	1 set for <u>+</u> 140 m2



GRC Tape

The function of GRC Tape is to cover and strenghten the join, also for intermediary between surface of GRC A+B compound and GRC Top Coat.

Unit	Dimension		
Dall	Length	<u>+</u> 45 m	
Roll	Width	2.5 centimeter	



GRC PUTTY

GRC PUTTY is a multipurpose white cement compound that can be applied for finishing joint and repair the wall.

Packaging	Weight	Descriptions
Zak	4 kg	for ± 4 m2
Zak	25 kg	for ± 25 m2





Nail & Screw

GRC Nail

GRC Nail is suitable to be applied on ceiling and partition which is fixed on by wood frame. GRC Nail is designed in such a way that it is equipped with the bigger and thinner head, so it's easy to be countersunk.

	Sachet	Box
GRC Galvanized Nail	400 gr	2 Kg & 30 Kg
GRC Non Galvanized Nail	400 gr	2 Kg & 30 Kg
Superplank Galvanized Nail	400 gr	2 Kg



GRC Screw

To fasten GRC board on metal frame (such as: Hollow, Metal Furring and Metal Stud).

	Sachet	Box
GRC Screw 4mm	+ 500 pcs	+ 2000 pcs
GRC Screw 5-8mm	± 500 pcs	± 2000 pcs
GRC Screw 9-15mm	± 100 pcs	<u>+</u> 1000 pcs
GRC Screw >15-20mm	± 100 pcs	± 1000 pcs

