



GRC board[®]



THE FINEST CHOICE IN FIBRE CEMENT BOARD

PRODUCT CATALOGUE



www.grcboard.com

SCAN HERE



E-BROCHURE



PT. Bangunperkasa Adhitamasentra

Is a fiber cement board manufacturer in Indonesia with the brand "GRC board". The first plant was located in Citeureup, west Java, this plant was established since 1992 and have started the production in 1994, and because of the increasing of customer's satisfaction to GRC board products, we established the second plant in 2010, which was located at Karawang and the third plant at Jombang East Java which started operating in 2020 to meet the demand of the market. The technology applied is from Japan and equivalent with international standards product quality.

The certification that has been obtained by GRC board is:

ISO 9001: 2015 for design/development and manufacture of non asbestos fiber cement boards.

SNI 1741-2008 for fire resistance equal to JIS 1304

ISO 140; Measurement of sound Insulation in building and Buildings element.

SNI 8299 Non asbestos flat cement board

Green Label Certificate from Green Product Council Indonesia



Ceiling Application

GRC board products can be used in interiors (protected from the weather) such as partition walls and ceilings.

GRC board is usually applied to office buildings, factories, hotels, schools, housing estates, apartments, hospitals, etc.

Thickness	3.5, 4, 4.5, 6 mm
Width	1220 mm
Length	2440 mm

Application for Partition, Roof Underlayer, Column Cover, etc

Thickness	6, 8, 10 mm
Width	1220 mm
Length	2440 mm

**Available for customized dimension & thickness with condition applied*



 **GRC board**®

Cladding Application

GRC Superpanel is a cement board product used for external wall applications, with a thickness that can provide panel characteristics that are strong and resistant to weather.

Size for Cladding Application :

Thickness	9, 12 mm
Width	1220 mm
Length	2440 mm

**Available for customized dimension & thickness with condition applied*



 **GRC SUPERPANEL**

Floor Application

Cement board with maximum thickness so that is strong enough to be used as a floor.

Size for Floor Application :

Thickness	15, 20 mm
Width	1220 mm
Length	2440 mm

**Available for customized dimension & thickness with condition applied*

Deck Application

Deck applications are intentionally finished by exposing the surface to either flat (GRC Super Deck) or wood grain (GRC Mahoni Deck) while for floor applications it is preferable to finish with ceramic, granite or parquet.



 **GRC Mahoni deck**

 **GRC Super deck**

Size for Deck Application :

Thickness	20 mm
Width	200, 300 mm
Length	2400 mm

**Available for customized dimension & thickness with condition applied*

Plank & Plint Application

GRC Superplank, GRC Simpleplank, GRC Rosewood plank and GRC Mahoni plank are cement board products that are manufactured in certain sizes for external applications such as listplank and sidding plank, have good weather resistance so they can be applied to the exterior.



 **GRC Mahoni plank**

 **GRC SUPERPLANK**

 **GRC SIMPLEPLANK**

Size for GRC Mahoni plank :

Thickness	8 mm
Width	100, 200, 300 mm
Length	2440, 3000 mm

Size for GRC Superplank :

Thickness	9 mm
Width	100, 200, 300 mm
Length	2440, 3000 mm

Size for GRC Simpleplank :

Thickness	8 mm
Width	100, 200, 300 mm
Length	2440, 3000 mm

**Available for customized dimension & thickness with condition applied*

GRC Deco plank is used for list plank applications to add aesthetic value to the building and make it look more ethnic.

Size for GRC Deco plank :

Thickness	9 mm
Width	200, 300 mm
Length	1200 mm

**Available for customized motive, dimension & thickness with condition applied*

GRC Rosewood plank is a cement board that has a natural wood grain texture, present to enrich choices for consumers who like the feel of wood in their building designs.

Size for GRC Rosewood plank :

Thickness	8 mm
Width	200, 300 mm
Length	3000, 4000 mm

**Available for customized dimension & thickness with condition applied*

 **GRC Rosewood Plank**

 **GRC Deco Plank**



Decorative Application


is a cement board product that can be used outdoors and indoors and serves as a building decoration to make it look more beautiful. In addition to the designs and sizes that are already available, consumers can order custom designs to choose size and thickness.



GRC Deco Panel®



Deco Panel Line




Size for GRC Deco Line :

Thickness	9 mm
Width	1200 mm
Length	2400 mm

**Available for customized dimension & thickness with condition applied*



Deco Panel Motive



Size for GRC Deco Panel Motive :

Thickness	6 - 20 mm
Width	1200 mm (max)
Length	2400 mm (max)

**Available for customized motive, dimension & thickness with condition applied*

Deco Panel Brick



Size for GRC Deco Brick :

Thickness	9 mm
Width	1200 mm
Length	2400 mm

**Available for customized dimension & thickness with condition applied*

GRC board Accessories



Compound A+B is a GRC glue that serves to fill the gap between the GRC board connection grout so the connection between GRC board will not cracked.

GRC Tape is a fiber tape that used to strengthen the connection. GRC tape is applied on the top of connection grout after apply Compound A+B.



GRC PUTTY is a Pre-mixed Mortar made from white cement which is specially formulated as a final coat or finish coat on various types of cement-based walls (GRC board, Plaster, Concrete) and is safe for use in interior and exterior areas.

GRC screw 4 mm

These screws are made for installation 4 mm GRC boards.

GRC screw 5 – 8 mm

These screws are made for installation 5mm to 8mm GRC boards and not recommended for boards 4mm thick.

GRC screw 9 – 15 mm

These screws are made for installation of products that have a thickness of 9 – 15 mm

GRC screw > 15 – 20 mm

These screws are made for installation of products that have a thickness of >15 – 20 mm



GRC nails are suitable for use on ceilings and partitions mounted on wood frames. GRC nails have designed a larger and thinner head, making them easy to countersunk.

GRC nails are finished galvanized (anti-rust), available in two types for board and plank application.





**MAKE SURE THAT GENUINE PRODUCT IS PRINTED
WITH "GRC BOARD" ON THE PRODUCT**

PRODUCT GUARANTEE

We guarantee that our products are sold in good condition without damage or fault caused by faulty production or its raw materials.

This product warranty does not cover damage caused by:

1. Transportation and/or its agent sending the goods to the customer as it is out of the company's control.
2. Installation quality and system of workers as various factors affect good and right installation system.
3. Suitability of our product on particular application which are not according to our recommendations



**Asbestos
Free**



Easy Application



Smooth Surface



Fire Resistant



Fungi Resistant



Strong & Durable



**Termite
Resistant**



**Moisture
Resistant**



Sound Insulation



member of :

Manufactured by:
PT. BANGUNPERKASA ADHITAMASENTRA
GRAHA GRC board
S. Parman street Kav. 64, 3rd floor, Jakarta Barat 11410
Phone : (021) 53 666 800 (hunting)
Fax. : (021) 53 666 720
Email : sales.export@grcboard.com